

TABLE 1

Calculated averaged location error values

Coordinate calculation algorithm	Average location error, m				Overall average location error
	146 MHz		434 MHz		
	City	Country	City	Country	
Maximum likelihood algorithm	90	60	50	40	60
Amplitude algorithm without taking into account a terrain relief	140	50	90	120	100
Amplitude algorithm with taking into account a terrain relief	100	40	50	120	78
Amplitude-goniometric algorithm	30	30	70	60	48

The results presented in Table 1 confirm that all three algorithms have accuracy of the signal transmitter location comprehensible to practice. Therefore, for a choice of the preferable algorithm it is necessary to consider additional factors.

Recommendations on use of methods and algorithms of DF in actual operating conditions of MMS

The practice shows that if the MMS includes high-speed radio equipment, the navigating equipment and the corresponding software, the combined method of a signal transmitter search is more often used that combines homing and DF during the movement. At such combination there is a continuous reception of radio signals that is important for DF of periodic or short-term transmissions. In addition, it provides an opportunity to use a multi-channel DF for determination of coordinates of several signal transmitters simultaneously and to provide security of DF operations because in this case the MMS moves in a common city traffic stream.

The maximum likelihood algorithm in application to a stand-alone MMS cannot calculate a signal transmitter coordinates under using of homing; therefore it is expedient to use the amplitude-goniometric algorithm working simultaneously with bearing and field strength level data. The additional reason in favor of the amplitude-goniometric algorithm is the fact that its operation is accompanied by a vivid display at a map of a zone that corresponds to the most probable position of a signal transmitter.

If the MMS is equipped only by a measuring receiver it is possible to use only amplitude algorithm which provides comprehensible accuracy at presence of a digital map giving terrain relief and blocks of buildings. Limitation of the amplitude algorithm is its low sensitivity and impossibility of operation at low signal-to-noise ratios.

For the MMS equipped by the DF, the algorithms based on processing of obtained bearings are applied. In comparison with the amplitude algorithm they provide greater accuracy of a signal transmitter coordinate determination spending shorter time. They also provide possibility of calculation of a signal transmitter coordinates under low signal-to-noise ratios and in situations when the signal transmitter is working in a short-term regime.

Therefore, for the stand-alone MMS equipped by FD and field strengths measurement capabilities, it is preferable to use the amplitude-goniometric algorithm. If the MMS does not equipped by field strength measurement facilities, the maximum likelihood algorithm is suitable. And, at last, if the MMS is equipped by only a measuring receiver only the amplitude algorithm can be used for the signal transmitter localization.

The literature

1. ITU Handbook. Spectrum Monitoring. Radiocommunication Bureau 2002
 2. Glaznev A.A., Kozmin V.A., Litvinov G.V., Shadrin I.A. Multi-station spectrum monitoring systems and localization of radio emission sources (in Russian, 2002) - http://ircos.ru/zip/spc_teh.pdf
 3. Ashihmin A.V., Kozmin V.A., Rembovsky A.M. Land mobile spectrum monitoring and direction-finding complexes (in Russian, 2002) – http://ircos.ru/zip/spc_teh.pdf
 4. Ashihmin A.V., Zhukov A.A., Kozmin V.A., Shadrin I.A. Localization of radio emission sources and field strength measurements of by a mobile monitoring station. (in Russian, 2003) - http://ircos.ru/zip/spc_teh2.zip
 5. Ashihmin A.V., Korovin A.G., Rembovsky A.M., Козьмин V.A. Distributed systems of spectrum monitoring and direction-finding (in Russian, 2006) – http://ircos.ru/zip/st5_06.pdf
 6. Kozmin V.A., Savelev A.M., Ufaev V.A., Chubov E.A. Comparison of methods of radio emission sources localization (in Russian, 2007) – http://ircos.ru/zip/st1_07.pdf
-